

MVRP SERIES ROTATING PADDLE LEVEL SWITCH

Product features



| | |
|-----------------------------|----------------------------------|
| Paddle material | : 1.4301 (304) stainless steel |
| Process connection material | : 1.4301 (304) stainless steel |
| Housing material | : Painted aluminium |
| Ambient temperature | : -20...+80 °C standard |
| Specific gravity | : > 0,5 g/cm ³ |
| Process pressure | : -0,5...+0,5 barg |
| Power supply | : 110 VAC / 220 VAC / 24 VDC |
| Output signal | : 1 x SPDT Contact (5 A 250 VAC) |
| Electrical connection | : 2 pcs M20 x 1,5 metallic plug |
| Rotating speed | : 5 rpm |
| Power consumption | : 4 W |
| Protection class | : IP65 |

Model coding

| MODEL | CONNECTION TYPE | POWER SUPPLY | VERSION | PADDLE TYPE |
|-------|------------------------|--------------|------------------------------------|---|
| MVRP | 30 G1" male thread | 1A 110 VAC | ST Standard HT High temperature | S1 Standard L Type V1 V Form X1 Cross |
| | 31 G1 1/2" male thread | 2A 220 VAC | | |
| | XX Special Req. | 2D 24 VDC | | |

Dimensions

